

External Battery Module (EBM)

FA00096

All IntelliPower systems utilize circuit boards, chassis, components and construction techniques that are specifically designed for extreme environments—rugged, challenging thermal and/or shock and vibration applications. Our digital, double conversion on-line UPS, power conditioner and frequency/voltage converter solutions utilize high-efficiency power switching and galvanic isolation, which provides ideal electrical output performance. Our standard build practices have enabled certified compliance to a number of performance standards for select models and product families. IntelliPower systems have proven performance in a wide range of key rugged military programs within the Army, Air Force, Navy and Marines. IntelliPower products are designed and manufactured in the USA, which means shorter lead times from design to shipping, as well as a level of personalized service unequaled in the marketplace.



External Battery Module (EBM)

Part #:	FA00096	Rev. 100121
Model #:	EBP-9LBFb-2U23	
Unit Description:	External Battery Module with Lead Acid Batteries, 108 VDC, 10.5 Ah	

CONNECTORS	
Connector(s) EBM/Charger Group 1 (type, location):	1 each MS3456L20-15S on a 12" pigtail, rear
MECHANICAL	
Enclosure Type & Size (type/rack unit, dimensions):	2U, rack mountable, 3.5 x 17 x 23 inch (Height x Width x Depth)
Enclosure Material & Finish (aluminum/steel, finish):	Aluminum, powder coated charcoal gray
Enclosure – Special (IP65/Zone 1):	N/A
Weight:	TBD
BATTERIES	
Battery Type (rating, PbAcid/Pure PbAcid/Lithium Iron):	12V10.5Ah Pb-Acid
Battery Total Quantity:	9

(continued)

Battery Strings (number of strings, quantity per string):	1, 9
Battery String Voltage:	108 VDC
Battery Runtime 1:	Approximately 8 minutes at 3000 Watts
Battery Mounting (Fixed/Hot Swap):	Fixed
EMI & ENVIRONMENTAL	
Temperature (Operating):	-20°C to 55°C
Humidity:	5 to 95% non-condensing

Specifications subject to change without notice.